

Application No.: 10/822,726

Docket No.: 2336-265

AMENDMENTS TO THE CLAIMS:

BEST AVAILABLE COPY

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A Wavelength Division Multiplexing (WDM) system for demultiplexing mixed optical signals ~~transmitted through one channel from the outside to distribute specific wavelength optical signals into a plurality of channels, said system~~ comprising:

a receiving optical fiber having an input end for receiving the mixed optical signals and an output end;

a filter arranged ~~[[in an]]~~ downstream of the output end of the receiving optical fiber for receiving the mixed optical signals from said output end and selectively transmitting a specific wavelength optical signal of a specific wavelength and identical with the peak wavelength of the filter but reflecting remaining wavelength optical signals of other wavelengths;

a lens positioned downstream of said filter and spaced from said filter by a gap;

a transmitting optical fiber positioned downstream of said lens for outputting the specific wavelength optical signal transmitted through the filter and said lens;

a shutter member moveable into and out of said gap for attenuating the specific wavelength optical signal transmitted between the filter and the ~~transmitting optical fiber~~ lens;

an actuator for driving the shutter member to move into and out of said gap and across ~~[[the]]~~ a propagation path of the specific wavelength optical signal ~~transmitted through the filter~~ in said gap; and

a control unit for controlling ~~the actuation of~~ the actuator.

Application No.: 10/822,726Docket No.: 2336-265

2. (original) The WDM system according to claim 1, wherein the filter is a dielectric thin film filter.

3-4. (canceled)

5. (currently amended) The WDM system according to claim 1, wherein the actuator is selected from the group consisting of a comb drive type Micro Electro-Mechanical System (MEMS) actuator and a scratch drive type MEMS actuator.

6. (canceled)

7. (currently amended) The WDM system according to claim 1, wherein the actuator is provided integrally in a main board ~~having~~ supporting the receiving and transmitting optical fibers.

8. (currently amended) The WDM system according to claim 1, further comprising a photodetector connected with ~~wherein the control unit is connected with a photodetector~~ for measuring the intensity of the specific wavelength optical signal attenuated by the shutter member and sending the measured intensity [[value]] to the control unit.

9. (original) A Wavelength Division Multiplexing (WDM) system for demultiplexing mixed optical signals transmitted through one channel from the outside to distribute specific wavelength optical signals into a plurality of channels, comprising:

a dual collimator having a receiving optical fiber for receiving the mixed optical signals;

Application No.: 10/822,726Docket No.: 2336-265

a filter arranged in an output end of the receiving optical fiber to selectively transmit a specific wavelength optical signal of a wavelength identical with the peak wavelength thereof but reflect remaining wavelength optical signals;

a single collimator having a transmitting optical fiber for outputting the specific wavelength optical signal transmitted through the filter;

a shutter member arranged between the filter and the single collimator to attenuate the specific wavelength optical signal transmitted through the filter;

an Micro Electro-Mechanical System (MEMS) actuator for driving the shutter member across the propagation of the specific wavelength optical signal transmitted through the filter; and

a control unit for controlling the actuation of the actuator.

10. **(currently amended)** The WDM system according to claim 9, wherein

the dual collimator includes a dual collimator pig tail for fixing the receiving optical fiber, a dual collimator GRIN lens attached to ~~an output side of the dual collimator pig tail~~ via a transparent adhesive member, and a dual collimator glass member ~~[[for]]~~ receiving therein the dual collimator pig tail, and ~~wherein~~

the single collimator includes a single collimator pig tail for fixing the transmitting optical fiber, a single collimator GRIN lens attached to ~~an output side of the single collimator pig tail~~ via a transparent adhesive member, and a single collimator glass member ~~[[for]]~~ receiving therein the single collimator pig tail.

11. **(currently amended)** The WDM system according to claim 9, wherein the shutter member is moveable into and out of ~~arranged opposite to~~ an air gap between a single GRIN lens of the single collimator and the filter, said air gap being formed in an adhesive member which coaxially couples the ~~for coaxially connecting~~ a single GRIN lens of the single collimator with the filter.

Application No.: 10/822,726

Docket No.: 2336-265

12. (canceled)

13. (currently amended) The WDM system according to claim 9 A Wavelength Division Multiplexing (WDM) system for demultiplexing mixed optical signals transmitted through one channel from the outside to separate specific wavelength optical signals into a plurality of channels, further comprising:

a dual collimator having a receiving optical fiber for receiving the optical signals;

a filter provided in an output end of the receiving optical fiber and coaxially attached to an output end of the dual collimator to selectively transmit a specific wavelength optical signal of a wavelength identical with the peak wavelength thereof but reflect remaining wavelength optical signals;

a single collimator having a transmitting optical fiber for outputting the specific wavelength optical signal transmitted through the filter;

a fixing tube having opposite ends and a middle region between said opposite ends, said filter being housed in the middle region of said fixing tube; and

a dual collimator glass member and a single collimator glass members member, which receive therein said dual collimator and said single collimator, respectively, and are mounted at the opposite on both ends of said fixing tube thereof to form an air gap between the filter and the single collimator -, the dual glass member receiving a dual pig tail of the dual collimator, and the single glass member receiving a single pig tail of the single collimator;

wherein said [[a]] shutter member is moveable into and out of said air gap for attenuating the specific wavelength optical signal transmitted through the air gap [[:]]

an Micro Electro Mechanical System (MEMS) actuator for driving the shutter member across the propagation of the specific wavelength optical signal transmitted through the filter;  
and

a control unit for controlling the actuation of the actuator.

Application No.: 10/822,726Docket No.: 2336-265

14. (currently amended) The WDM system according to claim 13, wherein the fixing tube has vent holes ~~perforated adjacent the opposite to both ends thereof to feed euring gas through the vent holes.~~

15. (currently amended) The WDM system according to claim 13, wherein the fixing tube has an opening located corresponding ~~perforated opposite to the air gap and so that~~ the shutter member is moveable ~~can move freely~~ through the opening into said air gap.

16. (new) The WDM system according to claim 1, wherein a space between said lens and said filter includes

a filled region filled with adhesive material which defines an adhesive member and couples the lens to the filter; and

a unfilled region free of said adhesive material and defining said gap.

17. (new) The WDM system according to claim 16, wherein said adhesive member is of a U shape having a central slot in which said shutter member is receivable.

18. (new) The WDM system according to claim 1, further comprising a fixing tube having axially opposite ends and a middle region between said opposite ends;

said filter and lens being housed in the middle region of said fixing tube;

the output end of the receiving optical fiber and an input end of the transmitting optical fiber being housed at the ends of said fixing tube, respectively;

wherein

the fixing tube has an opening through a circumferential wall thereof, said opening being located corresponding to the gap; and

the shutter member is moveable through the opening into said gap.

**Application No.: 10/822,726****Docket No.: 2336-265**

19. (new) A Wavelength Division Multiplexing (WDM) system for demultiplexing mixed optical signals, said system comprising:

a receiving optical fiber having an input end for receiving the mixed optical signals and an output end;

a filter arranged downstream of the output end of the receiving optical fiber for receiving the mixed optical signals from said output end and selectively transmitting a specific wavelength optical signal of a specific wavelength and reflecting optical signals of other wavelengths;

a lens positioned downstream of said filter;

a transmitting optical fiber having an input end, which is positioned downstream of said lens and spaced from said lens by a gap, and an output end for outputting the specific wavelength optical signal transmitted through the filter and said lens to the input end of said transmitting optical fiber;

a shutter member moveable into and out of said gap for attenuating the specific wavelength optical signal transmitted between the lens and the input end of said transmitting optical fiber;

an actuator for driving the shutter member to move into and out of said gap and across a propagation path of the specific wavelength optical signal in said gap; and

a control unit for controlling the actuator.

20. (new) The WDM system according to claim 19, wherein a space between said lens and the input end of said transmitting optical fiber includes

a filled region filled with adhesive material which defines an adhesive member and couples the lens to the input end of said transmitting optical fiber; and

a unfilled region free of said adhesive material and defining said gap.

**Application No.: 10/822,726****Docket No.: 2336-265**

21. (new) The WDM system according to claim 19, further comprising a pigtail for fixing the input end of said transmitting optical fiber adjacent said lens;

said pigtail and said lens having facing surfaces which define the gap therebetween and are inclined relative to the propagation path of the specific wavelength optical signal in said gap; and

said shutter method being moveable between said inclined surfaces.

22. (new) The WDM system according to claim 21, wherein the filter is a dielectric thin film filter.

23. (new) The WDM system according to claim 21, wherein the actuator is selected from the group consisting of a comb drive type Micro Electro-Mechanical System (MEMS) actuator and a scratch drive type MEMS actuator.

24. (new) The WDM system according to claim 21, further comprising a photodetector positioned downstream of the output end of said transmitting optical fiber and connected with the control unit for measuring the intensity of the specific wavelength optical signal attenuated by the shutter member and sending the measured intensity to the control unit.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**